

Wave Long-Range



Mechanical

Dimensions	Ø424.4 x 166.2 mm (Ø16.7 x 6.5")
Weight	Without mount: 2.59 kg (5.7 lb) With mount: 3.79 kg (8.4 lb)
Enclosure material	UV stabilized plastic
Mount material	Galvanized steel
Pole mount diameter	25 to 76.2 mm (1 to 3") on pipe outer diameter
Wind loading	286 N at 200 km/h (64.3 lbf at 125 mph)
Weatherproofing	IPX6

Hardware

Processor	Dual ARM® Cortex®-A53 cores at 1GHz
Memory	DDR3L 512MB
Networking interface	(1) GbE RJ45 port
Max. power consumption	18W
Power method	48VDC passive PoE 4-pairs (1, 2+; 3, 6-) (4,5+; 7, 8-) or 2-pairs (4, 5+; 7, 8-) 24VDC passive PoE 4-pairs (1, 2+; 3, 6-) (4, 5+; 7, 8-)
Power supply	48VDC, 0.65A gigabit PoE adapter (included) Can be powered by a UISP Router or UISP Switch
Button	Factory reset
LEDs	Power, Ethernet, GPS, link
Operating temperature	-40 to 60° C (-40 to 140° F)
Operating humidity	5 to 95% noncondensing
Certifications	FCC, IC, CE

Software

OS	airOS®
Operating mode	PtMP station
Ubiquiti specific features	Integrated 60 GHz radio, discovery protocol, Wave technology
Services	UISP, ping watchdog, NTP client, SNMP
Tools	Antenna alignment, discovery utility, ping, trace route, speed test
Network	Bridge/Router mode
Software management	Bluetooth management for easy setup over UISP app WEB UI
Minimum software requirements	Any modern web browser/iOS or Android based smartphone

System

Total throughput	2 Gbps (1 Gbps duplex)
Maximum range	8 km
Encryption	WPA2-PSK (AES)

RF

Operating frequency*	57 to 71 GHz <small>*Depends on regulatory region.</small>
GPS	Yes
Channel bandwidth	2160, 1080 MHz
Operating channels*	58320, 59400, 60480, 61560, 62640, 63720, 64800, 65880, 66960, 68040, 69120, 70200 MHz <small>*Depends on regulatory region.</small>
Modulation	16QAM, QPSK
Antenna gain	46 dBi
Azimuth and elevation beamwidth	3 dB: 0.8° 6 dB: 1.1°

Back-Up RF

WiFi standard	802.11ax (WiFi 6)		
Operating frequency*	US/CA	U-NII-1	5150 - 5250 MHz
		U-NII-3	5725 - 5850 MHz
	Worldwide	5150 - 5875 MHz	
	<small>*Depends on regulatory region.</small>		
Channel bandwidth	20, 40, 80 MHz		
Modulation	BPSK (1/2), QPSK (1/2), QPSK (3/4), 16QAM (1/2), 16QAM (3/4), 64QAM (2/3), 64QAM (3/4), 64QAM (5/6), 256QAM (3/4), 256QAM (5/6), 1024QAM (3/4), 1024QAM (5/6)		
Antenna gain	22 dBi		
Polarization	Dual-linear		
Cross-pol isolation	20 dB		
Azimuth and elevation beamwidth	3 dB: 8 to 10°		

LEDs

Power	Flashing white: bootup in progress White: not connected to UISP application Blue: connected to UISP application Flashing blue: locate in progress Blue/white: firmware upgrade in progress
Ethernet	Flashing blue: Ethernet traffic detected
GPS	Blue: receiving at least (4) GPS satellite signal
Links	White: 5GHz link Blue: 60GHz link



**EQUIPMENT
FOR SALE**

NEW Ubiquiti airFiber | Wave-LR | Access Points

AF60-XG | Wave-LR | U6+ | UAP-IW-HD



NEW IN BOX

Brand New in OEM Packaging

**Contact Today
For Current Inventory**

Visit [TELECOMCAULIFFE.com](https://www.telecomcauliffe.com)



✓ **REDUCING LEADTIMES**

✓ **COST SAVINGS**

✓ **LIFETIME WARRANTY**

✓ **SUSTAINABLE SOLUTIONS**



TELECOMCAULIFFE
A PICS TELECOM TEAM

BILL MCAULIFFE

Director of Sales – National Accounts

TEAMMCAULIFFE@PICSTELECOM.COM | 585.746.6383 | TELECOMCAULIFFE.COM