RADWIN SU-PRO 100 Series

Subscriber Unit - Data Sheet (RW5000/SU-Pro/5H00/F58/FCC/INT)



RW-5H00-0P58

Product Description

RW-5H00-0P58 is SU PRO, Integrated subscriber unit that delivers up to 100 Mbps net aggregate throughput and supports SLA (CIR) or Best-Effort service level.
SU PRO supports 5.1 to 5.8 GHz and complies with FCC/IC & FCC regulations.
The unit includes an integrated 22dBi antenna.

Product Highlights

- Up to 100 Mbps net aggregated throughput, upgradable to 250Mbps
- Long range Up to 40 km / 25 miles
- Guaranteed Service Level Agreement based on CIR or Best Effort Service level
- 22dBi antenna gain
- Short and constant latency
- Advanced MIMO, OFDM and Antenna Diversity
- Robust and reliable operation in harsh environmental conditions including obstructed line-of-sight scenarios
- IP-67
- Simplified installation using a Smartphone app.



Product Specifications:

Configuration							
Architecture	Outdoor Unit w	ith an integrated	antenna				
PoE to ODU Interface	Outdoor CAT-5	Outdoor CAT-5e; Maximum cable length: 100m for 10/100BaseT and 75m for 1000BaseT					
Radio							
Max Capacity	100 Mbps net a	100 Mbps net aggregate throughput; Upgradable to 250 Mbps with license key					
Range	Up to 40 km / 2	Up to 40 km / 25 miles					
Channel Bandwidth	Configurable: 10, 20, 40, 80 MHz (for the default band); Dynamic Channel BW selection (20/40/80 MHz)						
Modulation	MIMO-OFDM (BPSK/QPSK/16QAM/64QAM/256QAM)						
Adaptive Modulation & Coding	Supported						
DFS	Supported (FCC)						
Diversity	Supported						
Max Tx Power	21 dBm						
Duplex Technology	TDD						
Error Correction	FEC k = 1/2, 2/3, 3/4, 5/6						
Encryption	AES 128						
Support Indoor units	RADWIN PoE de	RADWIN PoE device (included in the package); pinout: (+) pins 4/5, (-) pins 7/8					
Uplink / Downlink Allocation	Configurable: Symmetric or Asymmetric						
Layer 2	HUB Mode						
QoS	Packet classification to 4 priority queues according to 802.1P or Diffserv						
VLAN Support	802.1Q, QinQ, 4094 VLANs						
ODU Management	IPv4/IPv6 dual-	stack; SNMP v1, S	SNMPv3; HTTP/H1	TTPS using web br	owser		
Supported Bands							
Band	CBW 10MHz	CBW 20MHz	CBW 40MHz	CBW 80MHz	Radio Compliance		
	[GHz]	[GHz]	[GHz]	[GHz]			
5.8 GHz FCC/IC (default)	5.730-5.845	5.730-5.845	5.730-5.845	5.730-5.845	FCC 47CFR Part 15.407; ISED RSS-247		
5.1 GHz FCC	5.170-5.250	5.170-5.250	5.170-5.250	5.170-5.250	FCC 47CFR Part 15.407		
5.2 GHz FCC	-	5.255-5.340	5.255-5.340	5.250-5.340	FCC 47CFR Part 15.407		
5.4 GHz FCC	-	5.480-5.715	5.480-5.715	5.485-5.715	FCC 47CFR Part 15.407		
5.1 GHz FCC	5.170-5.845	5.170-5.845	5.170-5.845	5.170-5.845	FCC 47CFR Part 15.407		
Mechanical							
ODU Dimensions	32.5(w) x 32.5(h) x 6.4(d) cm						
ODU Weight	2 kg / 4.41 lbs						
Power							
Power Feeding	Power provided over ODU-IDU cable						
Power Consumption	<9W						
Environmental							
Operating Temperatures	-35°C to 60°C / -31°F to 140°F						
Humidity	100% condensing, IP67 (totally protected against dust and against immersion in water up to 1m)						
Safety							
US/CAN (cTUVus)	UL 60950-1, UL 60950-22, CAN/CSA C22.2 60950-1, CAN/CSA C22.2 60950-22						
, (0.0.00)	EN/IEC 60950-1, EN/IEC 60950-22						
CE/IEC	EN/IEC 60950-1	., EN/IEC 60950-2					
	EN/IEC 60950-1	., EN/IEC 60950-2					
CE/IEC	,	Subpart B, Class					
CE/IEC EMC	47 CFR, Part15,		В				



Integrated Antenna						
Gain	22 dBi	22 dBi				
VSWR	2.0:1	2.0:1				
3 dB Azimuth Beamwidth	10 Deg. (typ)	10 Deg. (typ)				
Polarization	Dual Linear (Vertical and Hori	Dual Linear (Vertical and Horizontal)				
Sidelobes Level	-12 dB(typ)					
Cross Polarization	-25dB (typ)					
F/B Ratio	-25 dB	-25 dB				
Port To Port Isolation	30 dB (typ)	30 dB (typ)				
Lightning Protection	DC Grounded					
Antenna Pattern						
Elevatio	on @ 5.8GHz	Azimuth @ 5.8GHz				
-30 -40 -50 -60 -70 -80 -90 -100 -110 -120 -130 -140 -150 -160 -170	30 40 50 60 70 80 80 100 110 120 130 140	-50 -60 -70 -80 -90 -100 -110 -120 -130 -140 -150 -160 -170 -180 -170 -180 -170 -160 -170 -180 -170 -160 -170 -180 -170 -160 -170 -180 -170 -180 -180 -180 -180 -180 -180 -180 -18				

Ordering Info

Part Number: RW-5H00-0P58

Description: RADWIN SU-PRO 100 ODU, with an integrated antenna, supporting multi frequency bands at 5.x GHz, factory default 5.8 GHz FCC/IC.

Datasheet information can be changed by manufacturer without prior notice



EQUIPMENT FOR SALE

RADWIN 5000 RADIOS

JET PRO Base Stations & SU-PRO Subscriber Units

BRAND NEW

Large Quantities Available!



RADWIN

RAD-RW-5BG5-0650

RW5000/HBS-PRO/5BG5/F58/FCC/JET/INT

RAD-RW-5H00-0P58

RW5000/SU-PRO/5H00/F58/FCC/INT

Contact Today
For Current Inventory

Visit TELECOMCAULIFFE.com

- ✓ REDUCING LEADTIMES
- ✓ COST SAVINGS
- ✓ LIFETIME WARRANTY
- ✓ SUSTAINABLE SOLUTIONS



BILL MCAULIFFE

Director of Sales - National Accounts

TEAMMCAULIFFE@PICSTELECOM.COM | 585.746.6383 | TELECOMCAULIFFE.COM