

## **RADWIN Indoor Unit**

Indoor DC PoE device - Data Sheet

NO PICTURE AVAILABLE

RW-9921-2059

### **Product Description**

Indoor DC POE device for RADWIN radios, with GBE interface, supports input power range 10-60VDC.

### **Product Highlights**

- High power single port injector
- GBE compatible
- Power LED indication
- Full over current/voltage protections
- Non-vented case

## Product Specifications:

<b>ELECTRICAL</b>	
Input Voltage	10-60VDC
Input Current	10 to 60 VDC
Max. In-rush current	80A
DC Output Voltage	55VDC
<b>Environmental</b>	
Operating Temperatures	-40°C to +70°C (-40°F to 158°F)
IP Rating	Indoor
Humidity	0.95
<b>Safety</b>	
ETSI	IEC 60950-1
USA	UL 60950-1, CAN/CSA-C22.2 No.60950-1
UL	
<b>EMC</b>	
ETSI	EN 55022 Class B, EN 55024
FCC	FCC part 15 Subpart B Class B
<b>Mechanical</b>	
Case	Plastic
Dimensions	17(w) x 7(h) x 4.5(d) cm
Weight	0.292 kg / 0.64 lbs (without mounting kit)
Mounting kit	N/A
<b>Interfaces</b>	
PoE/ODU output	RJ45 GBE
Ethernet input	RJ45 GBE
Power cable	Terminal Block 3 pin

### Ordering Info

**Part Number:** RW-9921-2059

**Description:** Indoor DC POE device for RADWIN's radios, with GBE interface, supports power range of 10-60VDC.

EQUIPMENT  
FOR SALE

# RADWIN INDOOR DC POE DEVICES & LIGHTNING PROTECTION UNITS

**RAD-RW-9921-2059 (POE) & RAD-RW-9924-0107 (LPU)**



## RADWIN

Large Quantities  
Available!

Contact Today  
For Current Inventory

Visit [TELECOMCAULIFFE.com](http://TELECOMCAULIFFE.com)

✓ REDUCING LEADTIMES    ✓ COST SAVINGS    ✓ LIFETIME WARRANTY    ✓ SUSTAINABLE SOLUTIONS

**PICS** | **TELECOMCAULIFFE**  
A PICS TELECOM TEAM

**BILL MCAULIFFE**  
Director of Sales – National Accounts

TEAMCAULIFFE@PICSTELECOM.COM | 585.746.6383 | TELECOMCAULIFFE.COM